

Full HD
1080

A WORLD OF HIGH DEFINITION



1 Bacon cheese burger	\$6.50
2 Double burger	\$4.50
3 Hand-Tossed Pizza	\$18.00
4 Blends coffee & Concha	\$3.50
5 Chicken Nuggets	\$5.50
6 Cheese burger	\$6.50
7 Spicy Hotdog	\$3.00
8 Bacon Sandwiches	\$5.50



WUXGA
1920 X 1080P

RS232C
SERIAL CONTROL

SPDIF
DIGITAL SOUND

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE

PALLADINE

MULTIMEDIA LCD DISPLAY

PALLADINE



MULTIMEDIA LCD DISPLAY

WUXGA
1920 X 1080P

RS232C
SERIAL CONTROL

SPDIF
DIGITAL SOUND

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE



HOME ENTERTAINMENT

Though not built in with speakers or TV Tuner the EPT7000L, a high resolution/definition LCD display can be easily turn into your flat screen home entertainment TV with its multimedia connection. Just connect to your cable box, DVD recorder, or any appliances with TV Tuner. Add in your home audio systems and you have an extreme home theatre system.

COMMERCIAL APPLICATION

Supporting 1080p and WUXGA resolution up to 1920 x 1080 the EPT7000L/P come with multiple inputs like HDMI, DVI, VGA, RS232C, and etc, are equip for any commercial application. With a 70 inch display area and option for Portrait format, its ideal for digital advertising, information display, boardroom presentation and many other application needs.

READY FOR MULTI-SCREEN DISPLAY

The EPT7000L/P are also ready for multi screen display.



Full Screen



2 Way Display



3 Way Display



EPT7000L

Full HD
1080

EPT7000L/P LCD 70" MULTIMEDIA MONITOR

General Specifications

- Support Samsung 70" DID panel
- ATC (Automatic Temperature Control)
- HDMI/DVI-I Video Input
- 8xBLDC 80x25mm Cooling Fan
- Full HD Video (1080P) Support
- RS-232 Serial Control
- SPDIF Digital Sound Out (Optical-HDMI)

Panel

- Active Area (mm) : 1,549.44 (H) x 871.56 (V)
- Resolution : 1920x1080 (16:9)
- Brightness : 600CD (1500:1 CR)
- Optional High Brightness/Contrast available
- Interface : Dual Channel LVDS

Video/Audio

- Inputs : HDMI/DVI-I
- Signal : up to 1920x1080@60Hz
- SPDIF : Optical Out (HDMI)

DID Features

- RS232C : 19200BPS
- Temp. Sensor : Main(Default), Aux(Optional)
- Light Sensor : 0~2.4M Lux Detection (Option)
- Cooling Fans : 80x25mm BLDC - 8 Fans (ATC)
- Scheduling : Power Saving Scheduling (Option)

Power

- Circuit SMPS : 75W-12V
- Inverter SMPS : 300W-24V x 4 Units
- Input Voltage : AC90~245V(50/60Hz)
- Power Consumption : Max 1275W
- Stand-By Mode : 5W

Operating/Storage Condition

- Operating Temperature : 0°C~50°C
- Operating Humidity : 20%~90%RH
- Storage Temperature : -20°C~65°C
- Storage Humidity : 5%~90%RH

Dimension

- Size without stand (mm) : 1665(L)x990(H)x130(D)
- Size with stand (mm) : 1665(L)x1060(H)x280(D)
- Packing Size(mm) : 1820(L)x1160(H)x385(D)
- Net Weight : 118Kg

Options

AV Extender

- Video : Component, AV, S-Video
- Signals : up to 1080i, NTSC/PAL/SECAM
- Sound Input : PC, AV, Component Sound Input

Light Ambient Sensor & Cable

- Detection Range : 0 ~ 24 Million LUX
- Cable Length : 800mm

Aux Temperature Sensor & Cable

- Detection Range : -30°C~100°C
- Cable Length : 800mm
- Speaker Out : Bohm, 7Wx7W Stereo Out



EPT7000P PORTRAIT DISPLAY

Palladine
TECHNOLOGY

Palladine Technology Pte Ltd

10 Upper Aljunied Link, Johnson Controls Building #03-09, Singapore 367904

Tel: (65) 6858-6166 Fax: (65) 6858-6066 Email: sales@palladine.com

Copyrights Palladine Technology Pte Ltd. All other companies trademark and copyright remain the property of their owner.
Palladine Technology Pte Ltd disclaims proprietary interest in the mark and name of others.

7TH
Anniversary

www.palladine.com