




GENERAL SPECIFICATIONS			H-SERIES			L-SERIES				
			PLE4200HT	PLE3200HT	PLE3200H	PLED2400L	PLED2300L	PLED2200L		
										
LED PANEL	Display Size (inch)		42" WUXGA	32" WUXGA	32" WXGA	24" WUXGA	23" WUXGA	22" WUXGA		
	Display Area (mm)		930 x 523	698 x 393	698 x 393	531 x 299	509X286	477 x 268		
	Panel Type		FULL HD 100Hz (WUXGA)			HD READY	FULL HD			
	Resolution		1920 x 1080			1366 x 768	1920 x 1080			
	Color Depth	Colors	1.06 billion			16.7 Millions	16.7 Million			
		Bit	10 bit			8 bit	6 bit Hi FRC			
	Contrast Ratio		4000:1			2500:1	1000:1	1000:1	1000:1	
	Brightness		450 cd/m ²			300 cd/m ²	250 cd/m ²	250 cd/m ²	250 cd/m ²	
	Response Time		6.5 ms			6.5 ms	5 ms	5 ms	5 ms	
	Viewing Angle		178° H/ 178° V			176° H/ 176° V	160° H/ 170° V			
TV/A/V/PC/USB/Digital/LAN	TV Systems	TV Tuner	HD Digital	H.264 MPEG4			-----			
			Digital	HD DVB-T MPEG 2 for Australia (Optional)			-----			
			Analog	DVB-T			-----			
			Sound	PAL SECAM			Optional			
	Video Systems	Video Systems	MPEG-2 MP@HL, MPEG-4 AVC/H.264							
		Sound Systems	MPEG-1 Layer 1/2, MPEG 4 AAC/AAC-HE(AAC+)			-----				
		Video Definition	480i/p, 576i/p, 720p, 1080i, 1080p			480i/p, 576i/p, 720p, 1080i, 1080p				
	Sound	Systems	NICAM/A2, BG, DK, I							
		Output	2 x 9W (8Ω) - Built In Speakers			2x9w		2 x 3W (8Ω) - Built In Speakers		
	PC (Pixel)	Resolution (D-Sub/HDMI)	1920 x 1080			1366 x 768		1920 x 1080		
	USB Format	Audio & Video	Format	AVI/MKV/ASF/Quicktime/MPEG PS/TS			AVI/MPEG			
			Files Ext.:	.avi/.mkv/.asf/.wmv/.mov/.mp4/.vob/.mpg/.ps/.ts			.avi/.dat/.mov/.vob/.mpg			
			Video Codec	Divx, H.264, Xvid, H.264, MPEG-2/4, VC1, WMV3			DivX, Xvid, MPEG-1/2			
			Audio Codec	MP2/MP3/AAC/PCM/LPCM/WMA			MPEG1/2/WMA/AAC			
			Resolution	Up to 1080p subject to format type			SD			
Features	Picture	Files Ext.	JPEG/PNG/TIFF/BMP/GIF			JPG/JPEG				
	Teletext	1000 pages			1000 pages		10 pages			
INTERFACE	Input	TV	ATV/DTV	1 x IEC 75 Ohms			1 x IEC 75 Ohms			
		PC	RGB	1 x D-SUB			1 x D-SUB			
			Audio	1 x 3.5 mm Audio Jack			1 x 3.5 mm Audio Jack			
			USB	2.0	1 x USB		1 x USB		Optional	
		Audio & Video	HDMI	3 x Version 1.3			3 x Version 1.3		1 x Version 1.3	
			Component	1 set X 3.5mm extension			1 set X RCA Jack			
	Composite		1 set X RCA Jack			1 set X RCA Jack				
	Output	Audio	S-Video	1 x S-Video			-----			
			Coxial	1 X RCA jack			-----			
			A/V Output	-----		1 set X RCA Jack		1 set X RCA Jack		
	Headphone	1 x 3.5 mm Audio Jack			1 x 3.5 mm Audio Jack					
	Others	Card Reader	Optional (EU Version Only)			Optional (EU Version Only)				
OTHERS	Power	Supply	AC 100~240 (50/60 Hz)							
		Consumption	175W	120W	85W	55W	50W	35W		
		Standby	<1W	<1W	<1W	<1W	<1W	<1W		
	Dimension (W/H/D) (mm)	withoutStand	1022X47X634.5	778.4X48X491.5	766X36X475	585X51X382.6	TBA	540.4X48X354.2		
		with Stand	1022X256.5X702.5	778.4X202X541.2	766X200X528	585X170X441.5	TBA	540.4X170X414.3		
	Weight (KG)	Net	18.2	10.5	9.2	4.8	TBA	4		
Gross		21.5	13.5	12	7	TBA	6			
Container loaded qty		40HQ	380SETS	600SETS	600SETS	1600SETS	1600SETS	2200SETS		

* Specification and type of LED panel are subject to changes without prior notice.